

RECEIVED  
CENTRAL FAX CENTER

JUN 30 2006

IN THE CLAIMS:

## BEST AVAILABLE COPY

1. (Currently Amended) A filter for a drill string, comprising:

a perforated receptacle having an open end ~~opposite~~ and a perforated end;  
a flange extending perpendicularly from an axis of the receptacle and being attached to the receptacle adjacent the open end, the flange comprising first and second mounting surfaces;  
and  
an annular transmission element disposed in grooves formed in each of the first and second mounting surfaces,

wherein the respective transmission elements are in electrical communication with each other and with a transmission network integrated into the drill string.

2. (Original) The filter of claim 1 wherein each mounting surface comprises a groove which houses the transmission element.

3. (Currently Amended) The filter of claim 2 wherein at least one of the mounting surfaces comprise a passageway intersecting the groove and in fluid communication with the open end of the filter.

4. (Original) The filter of claim 2 wherein at least one of the grooves comprise a biasing element adapted to bias the transmission element towards an adjacent transmission element.

5. (Original) The filter of claim 1 wherein the transmission elements are selected from the group consisting of inductive couplers, direct electrical contacts, and optical couplers.

6. (Original) The filter of claim 1 wherein the transmission elements are connected by a third conductor forming a LC circuit.

## BEST AVAILABLE COPY

7. (Original) The filter of claim 6 wherein a capacitor modifies electrical characteristics of the LC circuit.
8. (Original) The filter of claim 1 wherein the perforated receptacle is corrosion-resistant.
9. (Currently Amended) The filter of claim 1 wherein the filter further comprises an electronic ~~an~~ component.
10. (Original) The filter of claim 9 wherein the electronic component is selected from the group consisting of a sensor, a router, a power source, a clock source, a repeater, an electronic processor, an integrated circuit, a network node, and an amplifier.
11. (Original) The filter of claim 1 wherein the filter further comprises a mandrel mounted coaxially within a central bore of the drill pipe and adapted for removing the filter.
12. (Currently Amended) A filter for a drill string, comprising:  
a perforated, corrosive resistant receptacle having an open end ~~opposite~~ and a perforated end;  
first and second mounting surfaces are formed by a flange which extends  
perpendicularly from an axis of the receptacle and are attached adjacent the open end; and  
a transmission element disposed within a groove in each of the first and second mounting surfaces,  
wherein the respective transmission elements are in communication with each other via an electrical conductor forming an LC circuit and with a transmission network integrated into the drill string.

## BEST AVAILABLE COPY

13. (Original) The filter of claim 12 wherein the mounting surfaces comprise a passageway intersecting the groove and in fluid communication with the open end of the filter.
14. (Original) The filter of claim 12 wherein the groove comprises a biasing element adapted to bias the transmission elements towards adjacent transmission elements.
15. (Original) The filter of claim 12 wherein the transmission elements are selected from the group consisting of inductive couplers, direct electrical contacts, and optical couplers.
16. (Original) The filter of claim 12 wherein a capacitor modifies electrical characteristics of the conductor.
17. (Original) The filter of claim 12 wherein the filter further comprises an electronic component.
18. (Original) The filter of claim 17 wherein the electronic circuitry is selected from the group consisting of a sensor, a router, a power source, a clock source, a repeater, an electronic processor, an integrated circuit, a network node, and an amplifier.
19. (Original) The filter of claim 12 wherein the filter further comprises a mandrel mounted coaxially within a central bore of the drill pipe and adapted for removing the filter.